

DESIG	DESIGN DRAWN BY PH		DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA
CHEC	CHECKED // APPROVED //		DRAWING NO. REV. B
	#	The state of	DSI 9235 SHEET 1 OF 1
DATE			TITLE SCALE
05.10.14			QUICK PIN REPLACEMENT NTS
Α		02.07.03	NEW ISSUE
В		05.10.14	LENGTHEN QUICK PIN FOR RE-DESIGN

DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS IIN-D206-628 REV. E

REF. CANADIAN STC: SH98-14 REF. FAA STC: SA00500SE

THE FOUR AN4-15A BOLTS USED TO ATTACH THE STEP TO THE MOUNTING LUGS MAY BE REPLACED WITH:


STAINLESS STEEL POSITIVE LOCKING QUICK RELEASE PINS WITH A MINIMUM DOUBLE SHEAR STRENGTH OF 2400 LBS, A 1.3 INCH GRIP LENGTH (MINIMUM), AND 0.25 INCH DIAMETER

POSSIBLE PARTS NUMBERS

BOLT	MINIMUM GRIP	POSSIBLE QUICK RELEASE PIN REPLACEMENT
AN4-15A	1.3" (33.0mm)	AVIBANK:BLC4B13S, BLC4TA13S, BLC4R13S, BLC4LA13S MS NUMBER:MS17984C413, MS17985C413, MS17986C413, MS17987C413 REID: BLRS-020, BLBS-020

THE FOLLOWING OPTIONAL KITS ARE AVAILABLE FROM DART TO PROVIDE QUICK RELEASE COMPATIBILITY:

QTY -011	PART NUMBER	DESCRIPTION
X	DSI9235-011	QUICK RELEASE PIP PIN KIT
4	BLRS-020	QUICK RELEASE PIN



Copyright © 2005 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.